





# KL480 Tiller

TRACTOR COMPATIBILITY KEY:

3400

4500



The KL480 Tiller is designed for easy preparation of gardens and yards. This power-driven front-end attachment allows the operator to easily monitor the Tiller's performance. Designed with the Ventrac Mount System, the Tiller can be attached in a minute or less and comes with a stand for storing the Tiller when not in use.

A number 80 chain in an enclosed final drive is lubricated for heavy-duty performance. Skid shoe adjustments facilitate cutting depth. Twenty-four high carbon steel tines are sequentially spaced to provide smooth and efficient tillage.



## STANDARD FEATURES

- Intermediate Gear Reduction for Quiet Running
- Sealed Lubrication Final Drive
- Leveler Shield
- Skid Shoe Adjustments
- 24 High-Performance Carbon Tines
- Stand for holding attachment when not in use
- Ventrac Mount System

## SPECIFICATIONS

Stock Code	39.55220
Working Width	48 inches (122 cm)
Tines	24
Maximum tilling depth	6 inches (15.24 cm)
Final Drive	#80 Chain, enclosed and lubricated
Ground Clearance	Approx. 10 inches (25.4 cm) raised

## Dimensions

Length	41 inches (104 cm)
Width	53 inches (135 cm)
Height	22 inches (56 cm)
Weight	356 lbs (162 kg)
Shipping Weight	425 lbs (193 kg)
Shipping Dimensions (L x W x H)	57x43x25 inches (145x109x64 cm)

All specifications subject to change without notice or obligation



500 Venture Drive  
Orrville, OH 44667  
1.866.836.8722

Fax: 330.683.0000  
www.ventrac.com  
info@ventrac.com